

Fabric-wrapped wall panels in SIZE ZERO

Soak Series now just 10mm thick. Wow!

Size Zero is the current fad so can Anutone's design+development team be far behind? Everybody wants it slim, superslim! After Size Zero laptops, smartphones, televisions and ramp models, comes the ultra-slim, ultra-chic Soak series of fabric-wrapped wall panels.

Soak Cordura, Cord & Plane earlier had a limitation of minimum thickness, 20mm. This was due to kerfed long edges to receive H-Spline. This also resulted in a site problem of panels being able to be dismantled from one corner only. Now to meet the demand from designers for space-saving slimmer panels, Anutone has innovated to result in 10mm thick panels that can be hung on walls and more importantly dismantled from any point. Also all edges are fully finished - so panels can be installed discretely as floating islands!

For additional airgap behind these Size Zero panels, Anutone's recent innovation of a very slim Strut channel, the CC10, comes in useful ([see e-news # 24 dated 22 September 2009](#)). And if this still does not satisfy you for sound absorption, Anutone's very slim Synth 5x10 and 10x10, fitted in the 10mm airgap, do the honours!

Launching January 2010!

Sneak a preview - [Soak Cordura Brochure](#)



Soak series – Size Zero - Highlights

Features	Benefits
Ultra-slim, ultra-chic – all edges finished	Architect
Discrete install - wall island floats	Architect
Space saving – 10mm thickness only	Builder
Economical – slim means less costs	Customer
Frequency response – additional bass	Acoustician
Matching accessories – slim channel & infill	Contractor
Snag-free - single source compatibility	Project Manager
Accessibility – any point dismantlable	Facility Manager

⚠ Denoted thickness are of base panel only. Please add fabric thickness and Z-clip/bar thickness to panel thickness to arrive at installed depth of system from base wall. For example, Soak Cord 10mm would mean minimum 18mm installed depth of system. Soak Cord on CC10 with/without Synth would mean 28mm installed depth. For true 10mm system thickness only go for [Slim PNS](#) or [Slim Compo](#) from Anutone!

[Download Soak Cordura Brochure](#). Anutone Interiors loops their e-newsletter every Tuesday morning. If you have missed previous issues please visit www.anutone.com/infobin/enewsletter.html or contact a Anutone rep.



ANUTONE INTERIORS

(a division of Anutone Acoustics Limited)

MUMBAI
mumbai@anutone.com
Office 022 26439732
Pritpal 9821079600
Bobby 9892504871
Sadashiv 9987094313

PUNE
Pritam 9420696810

DELHI
delhi@anutone.com
Office 011 24378061
Jiten 9811065605
Chandra 9811981501
Ajay 9899708056

KOLKATA
Pradeep 9880623510

CHENNAI
chennai@anutone.com
Office 044 28330906
Shabeer 9940070888
Navin 9840773888

BENGALURU
Rajesh 9845010814
Bharathi 9845867026

www.anutone.com

[Email to friend](#)

[Print this page](#)

All logos and names are the copyrights of the respective owners.
To ensure delivery to your inbox, please add info@anutone.com to your address book.
If you wish to stop receiving our emails, reply with Unsubscribe in the subject line to info@anutone.com.